# Any questions?

Contact us, we will be pleased to advise you.





## Headquarters

## **BMZ Germany GmbH**

Zeche Gustav 1 63791 Karlstein am Main Germany

P: +49 6188-9956-0

E: mail@bmz-group.com

## **BMZ USA Inc.**

1429 Miller Store Road Virginia Beach VA 23455 USA

P: +1-757 821-8494

E: contact-usa@bmz-group.com

#### BMZ Innovation Group Ltd.

Future Business Centre Kings Hedges Road Cambridge, CB4 2HY United Kingdom

P: +44 7391 351787

E: lukas.gazda@bmz-group.com

## BMZ Company Ltd.

Julong Technology Building B Cuibao Road, Longgang District, Shenzhen, Guangdong Province P.R.China 518116

P: +86 755 8977 5800

E: contact.cn@bmz-group.com

## BMZ Japan KK

Shitaya 1-6-5, Taito-ku, Tokyo, 110-0004 Japan

P: +81 35811 1973

E: tokio.kobayashi@bmz-group.com

## BMZ Poland Sp. z o.o.

Alberta Einsteina 9 44-109 Gliwice Poland

P: +48 327842 450

E: BMZPolandSales@bmz-group.com

## BMZ France S.A.R.L.

153 Boulevard Haussmann 75008 Paris France

P: +33 06 84 52 76 29

E: nicolas.noel@bmz-group.com

# BMZ SERVICE ESTABLISHED

# **POWER2GO**

Power - always and everywhere



# www.bmz-group.com



E-MOBILITY



DRIVE SYSTEMS





GARDENTOOLS







All rights reserved. Preliminary data sheet. Although we have taken great care in preparing this document, BMZ does not accept any responsibility for errors or omissions. All information included here may be changed at any time without prior notification.

RAGE

INDUSTRIAL

# No Socket? No Problem!

We like to use the powerbank for our smartphone in private. But what if more power is needed?

# Time for Power2Go!

Let's think bigger! Power2Go is created for demanding users. Designed to be dustproof and waterproof, Power2Go is a robust companion for all occasions.

Too heavy? No way! Carry it one-handed? You can do it easily! Power2Go impresses with its extremely high power density and weighs just 23 kg!

Power2Go replaces your stationary power connection. Devices with up to 3,600 W peak power can be operated with the Power2Go. Constant, long-term power output of 2,500 W. This all is Power2Go, your reliable power grid on the go.



10 W

15,000 min 2,280 min

1,000 W

1,200 W

1,200 W

2,200 W



360 min 200 min

150 min







TECHNICAL DETAILS	POWER2GO LIFE	POWER2GO WORK
Cell Type	Li-lon 21700	Li-lon 21700
Nominal Power	2,500 W	2,500 W
Max. Power	3,600 W	3,600 W
Charging Voltage	92-264 Vac	92-264 Vac
Charging Power	1,000 W	1,000 W
AC Output @230Vac	2x 2,500 W (Schuko plug)	1x 2,500 W (Schuko plug)
1x AC Input	Neutrik Powercon plug	Neutrik Powercon plug
2x DC Output	USB-A 10 W	
2x DC Output	USB-C PD 100 W	
1x DC Output	120 W Car plug	
Extras	Display, Flashlight, LED Indicator for current use	LED Indicator for current use
Net Weight	~23 kg	~23 kg
Dimensions	452x373x192 mm	471x507x227 mm
Operating Temperature	~10 to 65°C	~10 to 65°C
Case Material	Aluminium	Aluminium
IP Class	IP65	IP65
Certification	UN 38.3, CE, UL-ready	UN 38.3, CE, UL-ready
Charging by Solar Panels	<500 W	<500 W